

# Datasheet

## BenQ BL2411PT

60.96 cm / 24" IPS LC-Display

- WUXGA - 1920 x 1200 / 16:10
- IPS Panel with LED backlight
- Viewing Angle H/V 178°/178°
- Response time 5 ms (GtG)
- Height Adjustment 130 mm incl. Pivot



LED



|                       |  |
|-----------------------|--|
|                       | Model : BL2411PT   |
|                       | Art. No. / EAN Code : 9H.L99LA.TBE / 471 8755 03983 6  |
| <b>Panel</b>          | Type : 60.96 cm / 24" Wide TFT, IPS-Panel  |
|                       | Resolution : 1920 x 1200 / 16:10   |
|                       | Pixel pitch : 0.27 mm  |
|                       | Picture diagonal / -area (W x H) : 609.6 mm / 518 mm x 324 mm  |
|                       | Max. colors: 16.7 Mio.   |
|                       | Viewing angle H/V (CR>10) : 178°/ 178°   |
|                       | Contrast (static) : 1000:1   |
|                       | Contrast (dynamic) : 20 Mio.:1   |
|                       | Brightness : 300 cd/m <sup>2</sup>   |
|                       | Response Time : 5 ms (GtG)   |
| <b>Connection:</b>    | DP input : DP  |
|                       | DVI-D input : DVI-D (with HDCP-support)  |
|                       | 15 Pin D-Sub Connector : RGB   |
|                       | Headphone Jack / Audio Connector : Yes / Yes   |
|                       | Frequency H/V : 30 - 83 kHz / 50 - 76 Hz   |
| <b>Control</b>        | Controls : On/Off hard power switch, 5 sensor OSD buttons  |
|                       | Functions : contrast, brightness, sharpness, vertical and horizontal picture, phase, pixel clock, 1 user 3 pre-settings color temperature, 17 languages, OSD (position, time), input, reset, information |
| <b>Extra</b>          | Picture: Senseye® 3-technology   |
|                       | Speaker: 2x 1 Watt   |
|                       | Safety: Kensington Lock  |
|                       | Mounting: VESA 100 mm x 100 mm   |
|                       | Height adjust: 130 mm including Pivot  |
|                       | Swivel: -45°/+45° left / right   |
|                       | Tilt: -5° / +20°   |
|                       | Sensor: Eye Protect Sensor, Eco Sensor   |
| <b>Energy</b>         | Power Supply : internal  |
|                       | Voltage for operation: 90 ~ 264 VAC / 47 ~ 63 Hz   |
|                       | Power consumption (Eco Mode) : < 23 W  |
|                       | (Sleep Mode) : < 0.3W  |
| <b>Certification</b>  | Safety: TÜV GS, EN60950, CE  |
|                       | Ergonomic: TÜV Ergo, ISO9241-307, TCO 6.0  |
|                       | Environmental: Energy Star 6.0, EPAT Gold  |
| <b>Environment</b>    | Operation: + 5 ~ +40°C; 20 ~ 90% air humidity  |
|                       | Storage: -20 ~ +60°C; 10 ~ 90% air humidity  |
| <b>Characteristic</b> | Weight net: 6.7 kg   |
|                       | Housing color: Black   |
|                       | Dimension with base (H x W x D): 444 mm x 555 mm x 236 mm (HAS lowest)   |
|                       | Accessories: Power- / DVI- / Audio-cable, Quick guide/User manual-CD   |
|                       | Warranty Terms: 3 years on-site exchange   |

